

# WP1000A

## SPECIFICATIONS

| Model                           | WP1000A        |
|---------------------------------|----------------|
| Welding range (mm)              | 630-1000       |
| Standard reducers (mm)          | 800-900-1000   |
| Optional reducers (mm)          | 630-710        |
| Power supply                    | 380V/50Hz, 3PH |
| Total power                     | 26.5 KW        |
| Heating plate                   | 18.5 KW        |
| Planing tool                    | 4 KW           |
| Hydraulic station               | 4 KW           |
| Pressure adjusting range        | 0-16MPa        |
| MaxTemperature of heating plate | 270°C          |
| Temperature Deviation           | ±7°C           |



## FEATURING

For use on building sites, drain pipe laying, and in the workshop.  
Suitable for PE, PP, PVDF  
Precision welding steel clamping reducers, high-strength steel base with cylinder, provides stable heavy-duty performance.  
Planing tool with safety switch prevents unintentional operation.  
Durable and long life HSS blade.  
Heating plate with high quality PTFE coating, enables swift temperature control.

## STANDARD PARTS

|                   |                    |
|-------------------|--------------------|
| Machine frame     | 1 set              |
| Heating plate     | 1 set              |
| Planing tool      | 1 set              |
| Hydraulic station | 1 set              |
| Reducers          | 1 set (800-1000mm) |

Optional parts: data logging device

