



# WP630A

## SPECIFICATIONS

| Model                           | WP630A                      |
|---------------------------------|-----------------------------|
| Welding range (mm)              | 315-630                     |
| Standard reducers (mm)          | 315-355-400-450-500-560-630 |
| Power supply                    | 380V/50Hz, 3PH              |
| Total power                     | 10.1 KW                     |
| Heating plate                   | 7.5 KW                      |
| Planing tool                    | 1.5 KW                      |
| Hydraulic station               | 1.1 KW                      |
| Pressure adjusting range        | 0-10 MPa                    |
| MaxTemperature of heating plate | 270°C                       |
| Temperature Deviation           | ±7°C                        |



## FEATURING

- For use on building sites, drain pipe laying, and in the workshop.
- Suitable for PE, PP, PVDF
- Integrated die casting aluminum frame, high-strength steel base with cylinder, provides stable heavy-duty performance.
- Planing tool with full-gear transmission structure. Durable and long life HSS blade.
- Heating plate with high quality PTFE coating, enables swift temperature control.
- Hydraulic station of integrated enclosure shielding splash & dirt

## STANDARD PARTS

|                   |                   |
|-------------------|-------------------|
| Machine frame     | 1 set             |
| Heating plate     | 1 set             |
| Planing tool      | 1 set             |
| Hydraulic station | 1 set             |
| Reducers          | 1 set (315-630mm) |

Optional parts: Flange holder, Data logging device

